



CHERRY BOMB GALAXY PRODUCT SPECIFICATIONS

System Type	4.5" 3-way Outdoor In-Ground Speaker with Built-In 5.25" Subwoofer
Impedance (Nominal) ¹	8 ohm
Sensitivity dB @ 2.83 V / 1 M	84 dB
Sensitivity dB @ 1 W / 1 M ²	84 dB
Frequency Response (±3 dB) ³	54 Hz - 20 kHz
Frequency Response (±10 dB) ³	38 Hz - 22 kHz
Max. Program Power ⁴	128 W
Max. Continuous Power RMS ⁵	64 W
Max. SPL dB @ 1 M ⁶	102 dB
Tap Selector	Three-Position Rotary Knob
Transducer: Low-Frequency Driver	5.25" Polypropylene Cone with Butyl Rubber Surround
Transducer: Mid-Frequency Driver	4.5" Polypropylene Cone with Butyl Rubber Surround
Transducer: High-Frequency Driver	.75" Titanium Dome
Enclosure Material	Rotomolded LLDPE with an Extruded PVC Cosmetic Sleeve
Grille	Aluminum, Powder-Coated, Weatherized
Inputs	Wire leads
Colors	Black, Brown
Height	32.4 in / 823 mm
Diameter	10.8 in / 274.3 mm
Weight	22.3 lbs / 10.1 kg
Shipping Weight	25.8 / 11.7 kg
Packaging	One per box
Included Accessories	Cover Plate, Cover Plate Screws, Wire Nuts
IP-Rating	IP65
Certifications	CE, RoHS
TAA Compliant (Trade America)	No
BAA Compliant (Made in USA)	No

Description

The Rockustics Cherry Bomb Galaxy speaker reimagines high-impact outdoor audio in a sleek, bollard form factor. The Cherry Bomb Galaxy from SoundTube is a weatherized direct-burial speaker designed to enhance an outdoor landscape without compromising audio quality. The patented three-way design includes a 5.25" double-chamber, band-pass subwoofer, a 4.5" woofer, and a 0.75" tweeter all in one compact design. By including the subwoofer in the same cabinet that houses the midrange and tweeter, the Cherry Bomb Galaxy provides exceptional full-range sound without running into the typical phasing issues you have when installing a sub in a different location from the other speakers in a traditional system. This makes installation faster, easier, and provides cleaner, more accurate sound.

Features

- Patented 3-way system design offers phase-matched audio across all frequencies.
- Included subwoofer gives great low frequency performance down to 38 Hz (-10dB)
- System provides exceptional audio everywhere in the listening environment.
- Three-way design in a single cabinet allows for simplified installation and system set up.
- Small below ground portion means a smaller hole is required - less digging.
- Fully weatherized speaker system.
- Rotary tap switch for 70.7 / 100 V operation and 8 Ω bypass.

Transformer Taps

70.7 V	Output	100 V	Output
64 W	102 dB	64 W	102 dB
32 W	99 dB		

¹ Impedance listed per IEC 60268-5 with a minimum less than 80% the nominal impedance

² 1 W/1 M sensitivity determined using nominal impedance

³ Frequency response measured in half or full space as dictated by speaker mounting configuration

⁴ Max program power is 3 dB above max continuous power

⁵ Continuous power rating, EIA-426-B test

⁶ Max output based on max continuous power

SoundTube[®]

13720 W. 109th St.

Lenexa, KS 66215

Phone: 913.663.5600

Fax: 913.663.3200

Toll Free: 855.663.5600

www.soundtube.com

