



## OMNIPLANTER 6.5 SWEETSPOT PRODUCT SPECIFICATIONS

System Type	6.5" Omnidirectional Outdoor Planter Speaker with SweetSpot Dual-Tweeter Technology
Impedance (Nominal) <sup>1</sup>	4 ohm
Sensitivity dB @ 2.83 V / 1 M	92 dB
Sensitivity dB @ 1 W / 1 M <sup>2</sup>	89 dB
Frequency Response ( ±3 dB ) <sup>3</sup>	76 Hz - 19.5 kHz
Frequency Response ( ±10 dB ) <sup>3</sup>	65 Hz - 20 kHz
Max. Program Power <sup>4</sup>	140 W
Max. Continuous Power RMS <sup>5</sup>	70 W
Max. SPL dB @ 1 M <sup>6</sup>	107.4 dB
Transducer: Low-Frequency Driver	6.5" Dual VC Polypropylene
Transducer: High-Frequency Driver	(2) .75" Mylar Dome
Enclosure Material	Roto-molded, UV-stable polyethylene
Grille	Screen mesh cover
Inputs	Wire leads
Colors	Gray Granite or Terra Cotta
Height	17.25 in / 438.2 mm
Diameter	20.75 in / 527.1 mm
Shipping Weight	21.75 lbs / 9.87 kg
Packaging	One per box
Included Accessories	Wire Nuts
Certifications	CE, RoHS
TAA Compliant (Trade America)	Yes
BAA Compliant (Made in USA)	Yes

## Description

A fully functional 20 inch (508 mm) diameter planter with drainage holes, the OmniPlanter 6.5 is an omnidirectional 2-way speaker as well. It includes a dual voice coil 6.5" coax woofer and two .75" dome tweeters. OmniPlanters are constructed of UV-stable, rotation-molded polyethylene and are available in two colors. Rockustics SweetSpot models have both a Left and Right channel wire input, combining two channels of audio into a single-point stereo effect. Non-SweetSpot models have a standard single-channel mono input.

## Features

- Coaxial driver assembly with 6.5-inch (165.1 mm) dual voice-coil polypropylene woofer and dual 0.75-inch (19mm) mylar dome tweeters delivering 360° of dynamic stereo-effect audio
- UV-, scratch-, chlorine- and weather-resistant enclosure with professional-grade components for long-lasting performance and durability
- Planter design with a 20.75-inch (527.1 mm) round bowl designed to accommodate live plants and allow for drainage
- Constructed of rotation-molded, UV-stable polyethylene
- Color options: Granite Grey or Terra Cotta

<sup>1</sup> Impedance listed per IEC 60268-5 with a minimum less than 80% the nominal impedance

<sup>2</sup> 1 W/1 M sensitivity determined using nominal impedance

<sup>3</sup> Frequency response measured in half or full space as dictated by speaker mounting configuration

<sup>4</sup> Max program power is 3 dB above max continuous power

<sup>5</sup> Continuous power rating, EIA-426-B test

<sup>6</sup> Max output based on max continuous power

# OMNIPLANTER 6.5 SWEETSPOT

6.5" Omnidirectional Outdoor Planter Speaker with SweetSpot Dual-Tweeter Technology

